

# **Titebond<sup>®</sup>**

## **THE PRO'S ADVANTAGE<sup>™</sup>**



A unique, modified-acrylic formula that offers superior adhesion on all common construction materials. It is ideal for sealing doors, windows, soffits and awnings around vinyl, aluminum, stucco, wood, brick and glass. This sealant dries quickly and can be painted and stained within two to four hours of application. It is also de-aired for a smooth, uniform bead and cleans up with water when wet. Titebond All Siding Sealant exceeds the performance requirements for ASTM C920, C834 and TT-S-00230C.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
3301	White	10.1 oz	12	15	108
3311	Cape Gray	10.1 oz	12	15	108
3321	Almond	10.1 oz	12	15	108
3331	Brown	10.1 oz	12	15	108
3351	Clay	10.1 oz	12	15	108
3361	Cedar	10.1 oz	12	15	108

### Application Guidelines

<p>Application Temperature : Above 40°F</p> <p>Service Temperature : -15°F to 180°F</p> <p>Method of Application : Cartridge / Caulking Gun</p> <p>Cleanup : Clean with water and scrape dried excess</p> <p>Maximum Coverage :</p>	<p>Tooling Time : Approx 10 minutes for 1/4" Bead</p> <p>Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive</p>
---	--

1/4" Bead	3/8" Bead	1/2" Bead
32 ft.	13.5 ft.	7.5 ft.

### Product Features

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>*Excellent Adhesion to All Siding Materials</li> <li>*Superior Flexibility &amp; Durability of a Silicone</li> <li>*Easy Paintability &amp; Cleanup of an Acrylic</li> <li>*Effective Barrier to Air, Dirt, Insects, and Radon</li> </ul> | <ul style="list-style-type: none"> <li>*Meets Performance Requirements of ASTM C920 Class 25 and ASTM C834</li> <li>*Meets Performance Requirements of Federal Specification 230C Class A</li> </ul> |
|--|--|