



A durable, acrylic-latex formula specifically designed for repairing and sealing cracks in all asphalt surfaces. It provides a durable, weather-resistant seal that helps protect from oil, gas, grease, salt, water and ice damage. Its siliconized acrylic formula offers excellent adhesion and will not peel, crack or pull away from the repaired area. Titebond Blacktop Repair dries to a textured finish, extrudes easily and cleans up with water.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
3181	Black	10.1 oz	12	15	108

Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead	
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive	
Method of Application : Cartridge / Caulking Gun		
Cleanup : Clean with water and scrape dried excess		
Maximum Coverage :		
1/4" Bead	3/8" Bead	1/2" Bead
32 ft.	13.5 ft.	7.5 ft.

Product Features

*Fills and Seals Cracks in Asphalt Surfaces	*Meets Performance Requirements of ASTM C920 Class 25 and ASTM C834
*Durable, Resists Oil, Gas, Grease and Salt	*Meets Performance Requirements of Federal Specification 230C Class A
*Textured Formula Blends with Surface	
*Extrudes Easily and Cleans with Water	