



This one-component, advanced polymer sealant is formulated specifically for filling contraction or expansion joints and cracks in concrete decks and floors. Titebond Self-Leveling Concrete Joint Sealant is designed to flow easily and smoothly into concrete cracks and joints to provide a permanent and durable seal. Meets or exceeds Federal Specification TT-S-00230C, Type I, Class A, ASTM C920 Type S Grade P Class 25, Use T and M, CAN/CGSB-19.13-M87, Class 1-40-B-N and C-1-25-B-N.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
3191	Gray	10.1 oz	12	15	108
3192	Gray	29 oz	12	39	38

Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead	
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive	
Method of Application : Cartridge / Caulking Gun		
Cleanup : Clean with water and scrape dried excess		
Maximum Coverage :	1/4" Bead	3/8" Bead
	32 ft.	13.5 ft.
		1/2" Bead
		7.5 ft.

Product Features

*Excellent Adhesion and Flexibility	*Passes ASTM C920 Type S Grade P Class 25, Use T and M
*Smooth, Easy Flow	*Passes CAN/CGSB-19.13-M87 Class 1-40-B-N & C-1-25-B-N
*Perfect for Horizontal Concrete Joints/Cracks	*Passes Federal Specification TT-S-00230C Type I Class A
*Does Not Contain Solvents or Isocyanates	
*VOC-compliant	