



A siliconized acrylic formula specifically designed for repairing and sealing cracks in concrete steps, sidewalks and driveways, as well as mortar joints. It provides a durable, weather-resistant seal that helps protect from oil, gas, salt, water and ice damage. It offers excellent adhesion and will not peel, crack or pull away from the repaired area. Titebond Concrete Repair dries to a texture finish, extrudes easily and cleans up with water.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
3171	Gray	10.1 oz	12	15	108

Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive
Method of Application : Cartridge / Caulking Gun	
Cleanup : Clean with water and scrape dried excess	
Maximum Coverage :	

1/4" Bead	3/8" Bead	1/2" Bead
32 ft.	13.5 ft.	7.5 ft.

Product Features

*Fills and Seals Cracks in Concrete & Masonry	*Passes ASTM C920 Type S Grade P Class 25, Use T and M
*Durable - Resists Oil, Gas, Grease and Salt	*Passes CAN/CGSB-19.13-M87 Class 1-40-B-N & C-1-25-B-N
*Textured Formula Blends with Surface	*Passes Federal Specification TT-S-00230C Type I Class A
*Excellent Adhesion and Flexibility	
*VOC-compliant	