



A long-lasting, advanced polymer sealant formulated specifically for sealing aluminum, galvanized and vinyl clad gutters and downspouts. Titebond Gutter & Seam Sealant provides a highly weather-resistant seal against water, wind, dust and dirt while retaining its resiliency and flexibility for years. It offers excellent adhesion to wood, metal, aluminum, steel, plastics, masonry and glass.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
7321	White	10.3 oz	12	15	108
7331	Aluminum Gray	10.3 oz	12	15	108

Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead	
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive	
Method of Application : Cartridge / Caulking Gun		
Cleanup : Clean with water and scrape dried excess		
Maximum Coverage :	1/4" Bead	3/8" Bead
	32 ft.	13.5 ft.
		1/2" Bead
		7.5 ft.

Product Features

- *Designed for Gutters, Downspouts and Flashing
- *Superior Adhesion to Prevent Leaks
- *Remains Flexible in Extreme Temperatures
- *Weather-Resistant
- *Adheres to Wood, Metal, Masonry, Glass and Plastic
- *Paintable
- *Advanced Polymer