



A 100% silicone formula specifically designed to permanently seal high-moisture areas found in kitchens and baths. This highly flexible mildew-resistant sealant offers strong, watertight adhesion and will not shrink or discolor over time. Titebond Kitchen & Bath Sealant is safe for food preparation areas when fully cured and is unaffected by water, humidity or heat. It meets or exceeds Federal Specification TT-S-001543A, Class A and ASTM C920 Type S, Grade NS, Class 25.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
1601	White	10.1 oz	12	11	108
1611	Clear	10.1 oz	12	11	108
1621	Almond	10.1 oz	12	11	108

## Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead	
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive	
Method of Application : Cartridge / Caulking Gun		
Cleanup : Clean with water and scrape dried excess		
Maximum Coverage :	1/4" Bead	3/8" Bead
	32 ft.	13.5 ft.
		1/2" Bead
		7.5 ft.

## Product Features

- |  |  |
|--|--|
| *Flexible                              | *VOC Levels Meet SCAQMD Requirements   |
| *Will Not Shrink or Discolor Over Time | *Federal Spec TT-S-001543A Class A, TT-S-00230C, Passes ASTM C920 Type S Grade NS Class 25 |
| *Water Tight Adhesion                  |  |
| *Mildew Resistant                      |  |