



A quality, yet economical latex formula designed specifically for interior pre-paint preparation. Ideal for filling gaps around baseboards, moldings and mantels, as well as repairing cracks in plaster and drywall. It dries quickly and offers good adhesion to most common building materials. Titebond Painters Caulk offers a smooth, uniform bead that can be painted or stained with one coat. It is easy to extrude, cleans up with water and has no residual odor.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
7301	White	10.1 oz	12	15	108

Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead	
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive	
Method of Application : Cartridge / Caulking Gun		
Cleanup : Clean with water and scrape dried excess		
Maximum Coverage :	1/4" Bead	3/8" Bead
	32 ft.	13.5 ft.
		1/2" Bead
		7.5 ft.

Product Features

*25 Year Warranty	*VOC Levels Meet SCAQMD Requirements
*Fills Gaps, Seals Joints	*Federal Spec TT-S-001543A Class A, TT-S-00230C, Passes ASTM C920 Type S Grade NS
*Paintable	Class 25
*Stainable	