



Designed for both interior and exterior applications, this siliconized acrylic formula is ideal for back filling trim, repairing cracks and sealing joints. It provides a mildew-resistant, watertight seal for most construction and repair projects. Titebond Painters Plus Caulk is highly flexible and offers a smooth bead that can be painted or stained easily in one coat. It is easy to extrude, cleans up with water and has no residual odor. Exceeds the performance requirements of ASTM C834.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
8301	White	10.1 oz	12	15	108
8311	Almond	10.1 oz	12	15	108
8321	Brown	10.1 oz	12	15	108
8331	Clear	10.1 oz	12	15	108
8341	Gray	10.1 oz	12	15	108
8351	Woodtone	10.1 oz	12	15	108
8361	Black	10.1 oz	12	15	108
8371	Antique White	10.1 oz	12	15	108

Application Guidelines

Application Temperature : Above 40°F

Service Temperature : -15°F to 180°F

Method of Application : Cartridge / Caulking Gun

Cleanup : Clean with water and scrape dried excess

Maximum Coverage :

1/4" Bead	3/8" Bead	1/2" Bead
32 ft.	13.5 ft.	7.5 ft.

Tooling Time : Approx 10 minutes for 1/4" Bead

Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive

Product Features

*Watertight Seal

*Mildew Resistant

*Paintable

*Stainable

*Cleans up with water

*Passes ASTM C834 Requirements