

Titebond[®]

THE PRO'S ADVANTAGE[™]



Titebond Roof Cement Sealant is an all-weather, asphalt-based patching compound that is specifically designed and formulated to repair cracks, seams, gaps and holes in roofing materials. Use to set flashings, drip edges and roofing material edges and to install shingles and roll roofing. Ideal for repair and new construction roofing and exhaust pipes. Formulated to meet Federal Specification SS-C-153 C Type I. Compliance: ASTM D6511, SCAQMD Rule #1168.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
3211	Black	10.3	12	10	108
3212	Black	29	12	26	38

Application Guidelines

<p>Application Temperature : Above 40°F</p> <p>Service Temperature : -15°F to 180°F</p> <p>Method of Application : Cartridge / Caulking Gun</p> <p>Cleanup : Clean with water and scrape dried excess</p> <p>Maximum Coverage :</p>	<p>Tooling Time : Approx 10 minutes for 1/4" Bead</p> <p>Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive</p>
---	--

<u>1/4" Bead</u>	<u>3/8" Bead</u>	<u>1/2" Bead</u>
32 ft.	13.5 ft.	7.5 ft.

Product Features

- | | |
|--|---|
| <ul style="list-style-type: none"> *Stops roof leaks *Ideal for wet and dry conditions *Resists cracking *Will not run or bubble | <ul style="list-style-type: none"> *Complies to ASTM D511, SCAQMD Rule #1168 *Formulated to meet Federal Specification SS-C-153C Type I |
|--|---|