

# **Titebond<sup>®</sup>**

## **THE PRO'S ADVANTAGE<sup>™</sup>**



A versatile, 100% silicone formula designed for interior and exterior applications. Ideal for most construction, remodeling and repair projects including doors, windows, siding, vents, tubs, sinks and more. It forms a tough yet flexible seal that is watertight and mildew-resistant. Titebond 100% Silicone Sealant offers strong adhesion to most materials and can withstand extreme temperature changes. It has been certified to Federal Specification TT-S-001543A, Class A and passes ASTM C920 Type S, Grade NS, Class 25.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
2601	White	10.1	12	11	108
2611	Clear	10.1	12	11	108
2621	Almond	10.1	12	11	108
2631	Black	10.1	12	11	108

### Application Guidelines

Application Temperature : Above 40°F	Tooling Time : Approx 10 minutes for 1/4" Bead
Service Temperature : -15°F to 180°F	Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive
Method of Application : Cartridge / Caulking Gun	
Cleanup : Clean with water and scrape dried excess	
Maximum Coverage :	

1/4" Bead	3/8" Bead	1/2" Bead
32 ft.	13.5 ft.	7.5 ft.

### Product Features

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>*Mildew resistant</li> <li>*Watertight seal</li> <li>*Withstands extreme temperatures</li> <li>*Maintains color with age</li> </ul> | <ul style="list-style-type: none"> <li>*Excellent adhesion to most materials</li> <li>*Complies with FDA under 21 CFR 177.2600 for indirect food contact applications</li> </ul> |
|--|--|