

Titebond[®]

THE PRO'S ADVANTAGE[™]



Titebond WeatherMaster Sealant has been specifically formulated to outperform all other sealant technologies, including silicones, tripolymers and urethanes. This superior polymer formula provides the best possible performance on siding, windows, doors and vents. In addition to offering permanent flexibility, it provides unbeatable adhesion to wood, fiberboard, vinyl, aluminum, metal roofing, brass and other common building materials. WeatherMaster Sealant is available in over 170 colors, all of which match today's popular siding color, regardless of the material or manufacturer. If touch-ups are necessary, it is paintable in one hour after application. It is waterproof, extrudes in extreme weather conditions and is UV-resistant, making it the ideal choice for exterior applications. Safety is not compromised, as this sealant contains no solvents or isocyanates and is VOC-compliant.

Cat. No.	Color	Size	Unit / Casae	Ctn. Lbs	Casses / Pallet
44001	White	10.3	12	15	108
43991	Crystal Clear	10.3	12	10	108
44011	Translucent	10.3	12	10	108

Application Guidelines

<p>Application Temperature : Above 40°F</p> <p>Service Temperature : -15°F to 180°F</p> <p>Method of Application : Cartridge / Caulking Gun</p> <p>Cleanup : Clean with water and scrape dried excess</p> <p>Maximum Coverage :</p>	<p>Tooling Time : Approx 10 minutes for 1/4" Bead</p> <p>Working Surfaces : For best results surfaces should be clean, dry, and free from material that may deter adhesive</p>
---	--

1/4" Bead	3/8" Bead	1/2" Bead
32 ft.	13.5 ft.	7.5 ft.

Product Features

- | | |
|--|--|
| <ul style="list-style-type: none"> *Superior polymer technology *Applies easily in extreme weather conditions *Fills gaps up to 1 inch wide | <ul style="list-style-type: none"> *UV-resistant *Outperforms silicone, tripolymer and polyurethane sealants |
|--|--|